

A b

**Conductivity Meter Digital Table
With Conductivity Cell 199.99 Mhos/cm**

Range 1.999mM for 2mM
 Ranges 20μ,, to 200m 0.1μ Mhos/cm
 Range Mhos : 200 Micro Mhos/cm x 0.1 Micro Mhos/cm



**Conductivity Meter Digital Table
ATC Automatic Temperature Compensation
With Conductivity Cell 199.99 Mhos/cm**



Abron Exports
www.abronexports.com
www.abronexports.com

**AC-301-CA Conductivity meter Table Model
 ATC with conductivity cell wire 220v
 With Auto Temperature probe**

**AC-301-C Conductivity meter Table Model
 with conductivity cell wire 220v**

Range		0 to 1000m mhos/cm in 5 ranges
Accuracy		± 0.3% FS 200μ Mhos/cm 1% FS in last range
Resolution		0.1μ Mhos/cm
Measuring Frequency		1000 Hz
Temp. Compensation		0° C to 50° C manual
Cell Constant		0.4 to 1.6 adjustable
Function Selector		CHECK/COND/CELL CONSTANT
Digital Display		3½ digit LED Display
Power Supply		220 V ± 10% Hz AC
Accessories		1) Conductivity cell 2) Electrode stand 3) Dust cover 4) Instruction Manual

Range	0 to 1000m mhos/cm in 5 ranges
Accuracy	± 0.3% FS 200μ Mhos/cm 1% FS in last range
Resolution	0.1μ Mhos/cm
Measuring Frequency	1000 Hz
Temp. Compensation	0° C to 50° C Automatic
Cell Constant	0.4 to 1.6 adjustable
Function Selector	CHECK/COND/CELL CONSTANT Automatic Temperature Compensation
Digital Display	3½ digit LED Display
Power Supply	220 V ± 10% Hz AC
Accessories	1) Conductivity cell 2) Electrode stand 3) Temperature Probe 4) Dust cover 5) Instruction Manual

AC-301-SP Conductivity cell for meter spare
 AC-301-ST Conductivity cell stand for meter spare
 AC-301-T Temperature Probe ATC with banana plug with wire auto compensation for abron digital meters spare